



Enclosed Links Bars & Insulators



Enclosed Links from 100 - 840A

Rating A	Holes	Part Number	Cover Colour	Depth mm	Width mm	Length mm	Mounting D = DIN P = Panel	Sealable
100	5	A100/5	Black	49	50	69	P	Y
	5	A100/5R	Red	49	50	69	P	Y
	7	A100/7	Black	49	50	100	P	Y
	7	A100/7R	Red	49	50	100	P	Y
	7	A100/7FB	Black	49	57	85	P	Y
	7	A100/7FBR	Red	49	57	85	P	Y
	10	A100/10	Black	49	50	100	P	Y
	10	A100/10R	Red	49	50	100	P	Y
	14	A100/14	Black	49	50	128	P	Y
14	A100/14R	Red	49	50	128	P	Y	
100	4	NSWLINK	Black	69	56	82	P	Y
	4	VICLINK	Black	69	56	82	P	Y
125	8	DB35	Grey	46	27	75	D/P	N
140	3	T3140B	Black	52	46	65	P	Y
	3	T3140R	Red	52	46	65	P	Y
165	7	A165/7	Black	41	42	99	P	Y
	7	A165/7R	Red	41	42	99	P	Y
	7	A165/7BW	Black	41	42	99	P	Y
	7	A165/7BWR	Red	41	42	99	P	Y
	7	LT165/7	Cream	49	49	109	P	Y
310	10	FSPDB3C	Grey	64	47	101	D/P	N
335	2	FSPDB4C	Grey	80	39	146	D/P	N
350	7	A350/7	Black	52	46	120	P	Y
	7	A350/7R	Red	52	46	120	P	Y
	13	A350/13	Black	52	46	120	P	Y
	13	A350/13R	Red	52	46	120	P	Y
	7	LT350/7	Cream	58	60	131	P	Y
840	4	FSPDB5C	Grey	80	72	145	P	N



A100/5



A100/7FB



A100/10



NSWLINK



VICLINK



DB35



T3140R



A165/7



A165/7BW

Enclosed Links from 100 - 840A

Rating A	Holes	Part Number	Hole size & quantity										
			5	6	7	8	9	12	15	20	24	Line Taps	
			Recommended maximum cable size										
			10mm ²	16mm ²	25mm ²	35mm ²	50mm ²	70mm ²	120mm ²	185mm ²	300mm ²	35mm ²	120mm ²
100	5	A100/5		3	2								
	7	A100/7		4	3								
	7	A100/7FB		4FW		3BW							
	10	A100/10		7	3								
	14	A100/14		11	3								
100	4	NSWLINK	2		2								
	4	VICLINK	1		1		2						
125	8	DB35	6	1		1							
140	3	T3140B				3							
165	7	A165/7		2	2	1		2					
	7	A165/7BW		2	2	1		2					
	7	LT165/7		3		2						2	
310	10	FSPDB3C				8		1		1			
335	2	FSPDB4C								2			
350	7	A350/7		1		2		2	2				
	13	A350/13	2	8		1			2				
	7	LT350/7		1		2	2						2
840	4	FSPDB5C									4		

Accessories for FS links

FSCAP2 - Sealingcap for spare spaces up to 185mm²

FSCAP3 - Sealingcap for spare spaces up to 300mm²

FSPIN1 - Multipole pins to join blocks



LT165/7



FSPDB3C



FSPDB4C



A350/7



A350/13R



LT350/7



FSPDB5C



ACCESSORIES

Neutral/Earth Bars & Insulators



NEUTRAL BAR



EARTH BAR

NEUTRAL BARS

Description	Bar Lengths (mm)	Part No.
Neutral Bars		
6 WAY	100	NB6-K
12 WAY	143	NB12-K
18 WAY	185	NB18-K
24 WAY	227	NB24-K
30 WAY	270	NB30-K
36 WAY	310	NB36-K
42 WAY	353	NB42-K
48 WAY	395	NB48-K
60 WAY	485	NB60-K
72 WAY	570	NB72-K
84 WAY	654	NB84-K
96 WAY	738	NB96-K

EARTH BARS

Description	Bar Lengths (mm)	Part No.
Earth Bars		
6 WAY	100	EB6
12 WAY	143	EB1
18 WAY	185	EB18
24 WAY	227	EB24
30 WAY	270	EB30
36 WAY	310	EB36
42 WAY	353	EB42
48 WAY	395	EB48
60 WAY	485	EB60
72 WAY	570	EB72
84 WAY	654	EB84
96 WAY	738	EB96



STAND-OFF INSULATORS

Height mm	Diameter mm	Threaded Insert	Test Voltage	Part No.
25	30.0	M6	0.66kV	SD125
35	32.0	M8	1kV	SD135
54	44.5	M8	0.66kV	14NB1
51	63.5	M10	0.66kV	14NB5
76	50.0	M10	1.5kV	SD176



National Customer Support Centre

Tel: 1300 556 601 Fax: 1300 550 187 www.ipdgroup.com.au



Quality Endorsed Company

AS/NZS 9001:2000
QEC 0228
SAI Global